

TRUCARE EXTERIOR WALL PRIMER

WATER THINNABLE

ASIAN PAINTS TRUCARE EXTERIOR WALL PRIMER IS A WATER-BASED WALL COATING SUITABLE FOR APPLICATION ON EXTERIOR AS AN UNDERCOAT TO EXTERIOR EMULSIONS.



PRODUCT BENEFITS

Asian Paints TruCare Exterior Wall Primer has good opacity and whiteness, which helps improve the appearances of the emulsion topcoats. Exterior Wall Primer does not chalk and can be applied on freshly plastered surfaces that are adequately cured. TruCare Exterior Wall Primer does not require any water curing.

PRODUCT FEATURES


AVAILABLE PACKS



1 ltr 4ltr 20 ltr

Shelf-life: 3 years from date of manufacture in original tightly closed containers kept away from direct sunlight and excessive heat.

SHADE RANGE



White

COVERAGE

On normal masonry surface by brushing:



**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

RECOMMENDED USAGE



Asian Paints TruCare Exterior Wall Primer can be applied on a wide range of exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. as an undercoat.

RECOMMENDED APPLICATION

CLEANING: Ensure that the surface to be painted is free from any loose paint, or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.

FILLING: Application of any kind of putty is not recommended. Surface imperfections such as holes, dents, cracks are to be filled only by using mixture of white cements & fine sand (in the ratio 1:3).

Freshly-plastered surfaces must be allowed to cure completely. Apply as follows:

PRODUCT	CODE	THINNER	DILUTION% (BY VOL)	APPLICATION VISCOSITY (SEC)	RECOATING* PERIOD (HRS)
<ul style="list-style-type: none"> Asian Paints TruCare Exterior Wall Primer Brush, Spray 	0065	 Water	 5-18  33	 15-18  33	4 hrs

*Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.



ADDITIONAL INFORMATION

POST PAINTING CARE

For the best performance of the paint, if left as such for a longer time before the application of the final coat, ensure that it is cleaned properly.

TECHNICAL DETAILS

- | | |
|---|---------------------------------|
| a) Drying Time | : Surface Dry time - 30 minutes |
| b) Gloss Levels/Sheen Levels | : NA |
| c) Flash Point (IS 101/1987, Part 1, Sec 6) | : NA |
| d) Stability of Thinned Paint | : Use within 24 hrs. |

PRECAUTIONS

- > Kindly refer to the MSDS for Asian Paints TruCare Exterior Wall Primer which gives detailed information on safety measures while handling the paint.
- > Do not apply when ambient temperature is less than 10° C or if the temperature might drop to this level within 4 hrs of application.
- > Do not overthin or overextend the brush.
- > Do not use Apcolite Universal Stainers or any other colourants.
- > Stir well and strain before use.
- > In coastal areas it is not recommended to leave the primer without the application of the topcoats for a long period of time.

SAFETY AND ENVIRONMENT FEATURES

- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- > In case of skin contact, immediately wash skin with soap and plenty of clean water. Get medical attention, if irritation develops or persists.
- > Do not breathe vapor or spray. It is recommended to wear mask during sanding and surface preparation to avoid dust inhalation.
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth and dispose through authorized agency for waste management.
- > No added Lead, Mercury, Arsenic, Chromium & Ammonia compounds.
- > Left-Over paint disposal:
 - Left-over paint/drums should not be disposed in soil/drains. Consumer should consult a local recycling agency for disposal of paint/drums.
 - The pails/drums should not be used for storing food items.



For enquiries, feedback and complaints, please call toll-free number 16600124680/9802033515 or write to us at weassure@asianpaints.com.np