

APEX ULTIMA

ASIAN PAINTS APEX ULTIMA IS A WATER BASED, WEATHER-PROOF, ANTI ALGAL AND HIGH PERFORMANCE EXTERIOR WALL FINISH WITH 7 YEARS PERFORMANCE WARRANTY.



 WATER BASED



 **No Added Mercury, Arsenic & Chromium**

Lead contents does not exceed 90 parts per million.

PRODUCT BENEFITS

Asian Paints Apex Ultima incorporates the latest state-of-art technology to provide long-lasting exterior performance even in the most extreme tropical conditions of India. Its unique advanced anti algal chemistry ensures that exterior walls are provided with power-packed resistance against algae and fungi growth. It has very good dirt pick up resistance and dirt cleaning properties.


PRODUCT FEATURES

AVAILABLE PACKS



Shelf-life: 3 years from date of manufacture in original tightly closed containers kept away from direct sunlight and excessive heat.

SHADE RANGE



Currently available in more than 1200 shades as per the Asian Paints Colour Palette.

COVERAGE

On smooth primer masonry surface by brushing



1 COAT
130 sqft/ltr-
150 sqft/ltr



2 COATS
65 sqft/ltr-
75 sqft/ltr

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

RECOMMENDED USAGE

Asian Paints Apex Ultima is an exterior wall finish that can be applied on various types of exterior cement plasters, asbestos sheets, concrete structures. Product cannot be applied on surfaces/substrates that are subjected to continuous seepage or dampness.
















RECOMMENDED APPLICATION

CLEANING: Ensure that the surface to be painted is free from any loose paint, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.

FILLING: Surface imperfections such as holes, dents, fine cracks are to be filled with Asian Paints Wall Putty or a mixture of white cement and fine sand (in the ratio of 1:3).

Freshly-plastered surfaces must be allowed to cure completely.

Apply top-coats as follows:

PRODUCT	CODE	THINNER	DILUTION% (BY VOL)	APPLICATION VISCOSITY (SEC)	RECOATING* PERIOD (HRS)
• Asian Paints Exterior Wall Primer Brush, Spray	0065	 Water	 90-110  40-45	 15-18  33	4 hrs
• Asian Paints Apex Ultima 1st Coat Brush, Roller, Spray	0012	 Water	 35-45  35-45	 35-45  35-45	4-6 hrs
• Asian Paints Apex Ultima 2nd Coat Brush, Roller, Spray	0012	 Water	 35-45  35-45	 35-45  35-35	4-6 hrs

*Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.

For best results, use Asian Paints Exterior Sealer, when the underlying surface exhibits chalkiness in spite of thorough surface cleaning.

 Spray  Brush

ADDITIONAL INFORMATION

POST PAINTING CARE

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any, at regular intervals of six months.

TECHNICAL DETAILS

- a. Drying time : Surface dry time 30 mins.
- b. Sheen levels : 25-40 at 85° GH
- c. Flash point (IS101/1987, Part 1, Sec 6) : NA
- d. Stability of thinned paint : Use within 24 hours

PRECAUTIONS

- > Kindly refer to the MSDS for Asian Paints Apex Ultima which gives detailed information on safety measures while handling the paint.
- > Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- > Do not over-thin or over-extend the brush.
- > Do not use Apcolite Universal Stainers or any other colourants.
- > Stir well and strain before use.
- > Tinted paints need thorough shaking immediately after tinter addition as well as before use.
- > Excessive bird droppings/spitting may affect the performance of the product.

SAFETY AND ENVIRONMENT FEATURES

- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- > In case of skin contact, immediately wash skin with soap and plenty of clean water. Get medical attention, if irritation develops or persists.
- > Do not breathe vapor or spray. It is recommended to wear mask during sanding and surface preparation to avoid dust inhalation.
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth and dispose through authorized agency for waste management.
- > No added Mercury, Arsenic, Chromium & Ammonia compounds.
- > Left-Over paint disposal:
 - Left-over paint/drums should not be disposed in soil/drains. Consumer should consult a local recycling agency for disposal of paint/drums.
 - The pails/drums should not be used for storing food items.



For enquiries, feedback and complaints,
please call toll-free number
16600124680/9802033515 or write to us at
weassure@asianpaints.com.np